



„CVD“ FOR MILLING NON-FERROUS MATERIALS

Solid carbide end mills with sharpest CVD-cutting edges and highest tool life



pokoIm

PREMIUMTOOLS. WE KNOW HOW.



SUPERHARD CUTTING MATERIALS CVD

Ball nose end mills | CVD | 2 flutes

2 flutes, plain shank, right hand

- center cutting end mill
- ball nose
- with clearance between shank and flute up to 5 x d
- high precise: r = +/- 0.005 mm ; d1 = h7

Ball nose end mills	catalogue no.	Effective working length at X° of draft													γ (chip angle)	λ (helix angle)	Features	Q/C
		d ₁ *	l ₂	l ₃	d ₃	l ₁	r	d ₂	z	0.5°	1°	1.5°	2°	3°				

wd. long																		
	B2NC-020-100-100-01	2	2.5	10	1.9	50	1	4	2	10.50	10.62	10.72	10.79	10.91	0	0		CVD
	B2NC-020-100-100-02	2	2.5	10	1.9	75	1	6	2	10.50	10.62	10.72	10.79	10.91	0	0		CVD
	B2NC-030-150-100-01	3	2.5	10	2.8	75	1.5	6	2	10.57	10.67	10.75	10.82	10.92	0	0		CVD
	B2NC-040-200-200-01	4	2.5	20	3.8	75	2	6	2	10.57	10.67	10.75	10.82	10.92	0	0		CVD
	B2NC-060-300-200-01	6	6	20	5.6	100	3	6	2	-	-	-	-	-	0	0		CVD
	B2NC-080-400-200-01	8	6	20	7.6	100	4	8	2	-	-	-	-	-	0	0		CVD
	B2NC-100-500-300-01	10	8	30	9.6	100	5	10	2	-	-	-	-	-	0	0		CVD
	B2NC-120-600-350-01	12	9	35	11.6	107	6	12	2	-	-	-	-	-	0	0		CVD

* further diameters on request

Cutting speed (V_c in m/min) | Feed per tooth (f_z) | d.o.c. (a_p) | w.o.c. (a_e)

Material	V _c (m/min)	a _p x d ₁ (mm)	a _e x d ₁ (mm)	Feed per tooth f _z (mm)							Cooling	Direction of feed
				Ø 2	Ø 3	Ø 4	Ø 6	Ø 8	Ø 10	Ø 12		
AlSi <12% Si	1800	0.2	0.1	0.01	0.02	0.02	0.04	0.06	0.08	0.1	Emulsion / MQL	climb milling
AlSi >12% Si	800	0.15	0.1	0.01	0.01	0.02	0.03	0.05	0.06	0.08		
Glass ceramic	250	0.1	0.15	0.025	0.035	-	-	-	-	-		
PMMA Acryl	1100	0.15	0.15	0.01	0.015	0.02	0.03	0.05	0.07	0.09	Emulsion recommended	climb milling
PF66 – GF30	700	0.15	0.1	0.008	0.01	0.015	0.025	0.04	0.06	0.08		
PEEK – GF30	700	0.15	0.1	0.007	0.008	0.01	0.02	0.03	0.05	0.07		
POM – GF30	800	0.15	0.15	0.008	0.01	0.015	0.025	0.04	0.06	0.08		
PTFE – GF30	700	0.15	0.1	0.01	0.015	0.02	0.03	0.05	0.07	0.09		
CFK	250	0.15	0.1	0.008	0.01	0.015	0.025	0.04	0.06	0.08	optionally air / MQL	climb milling / conventional milling
GFK	500	0.15	0.1	0.01	0.015	0.02	0.03	0.05	0.07	0.09		
AFK Aramid	300	0.15	0.1	0.01	0.015	0.02	0.03	0.05	0.07	0.09		
Zirkon	150	0.15	0.15	0.01	0.02	0.02	0.04	0.06	0.08	0.10		

SUPERHARD CUTTING MATERIALS CBN

Corner radius end mills | CVD | 2 flutes



2 flutes, plain shank, right hand

- center cutting end mill
- with clearance between shank and flute up to 5 x d
- high precise: r = +/- 0.005 mm ; d1 = h7

corner radius end mill	catalogue no.	d ₁ *	l ₂	l ₃	d ₃	l ₁	r	d ₂	z	Effective working length at X° of draft					γ (chip angle)	λ (helix angle)	Features	QC
										0.5°	1°	1.5°	2°	3°				

wd. long		d ₁ *	l ₂	l ₃	d ₃	l ₁	r	d ₂	z	0.5°	1°	1.5°	2°	3°	γ (chip angle)	λ (helix angle)	Features	QC
	C2NC-020-020-100-01	2	2.5	10	1.9	50	0.2	4	2	10.66	11.02	11.41	11.83	12.78	0	0		CVD
	C2NC-030-020-100-01	3	2.5	10	2.8	75	0.2	6	2	10.85	11.22	11.62	12.05	13.01	0	0		CVD
	C2NC-030-050-100-01	3	2.5	10	2.8	75	0.5	6	2	10.84	11.22	11.62	12.01	12.94	0	0		CVD
	C2NC-040-020-200-01	4	2.5	20	3.8	75	0.2	6	2	21.19	21.92	22.70	23.50	-	0	0		CVD
	C2NC-040-050-200-01	4	2.5	20	3.8	75	0.5	6	2	21.18	21.90	22.67	23.50	-	0	0		CVD
	C2NC-060-020-200-01	6	6	20	5.6	100	0.2	6	2	-	-	-	-	-	0	0		CVD
	C2NC-060-050-200-01	6	6	20	5.6	100	0.5	6	2	-	-	-	-	-	0	0		CVD
	C2NC-060-100-200-01	6	6	20	5.6	100	1	6	2	-	-	-	-	-	0	0		CVD
	C2NC-080-020-200-01	8	6	20	7.6	100	0.2	8	2	-	-	-	-	-	0	0		CVD
	C2NC-080-050-200-01	8	6	20	7.6	100	0.5	8	2	-	-	-	-	-	0	0		CVD
	C2NC-080-100-200-01	8	6	20	7.6	100	1	8	2	-	-	-	-	-	0	0		CVD
	C2NC-100-020-300-01	10	8	30	9.6	100	0.2	10	2	-	-	-	-	-	0	0		CVD
	C2NC-100-050-300-01	10	8	30	9.6	100	0.5	10	2	-	-	-	-	-	0	0		CVD
	C2NC-100-100-300-01	10	8	30	9.6	100	1	10	2	-	-	-	-	-	0	0		CVD
	C2NC-120-020-350-01	12	9	35	11.6	107	0.2	12	2	-	-	-	-	-	0	0		CVD
	C2NC-120-050-350-01	12	9	35	11.6	107	0.5	12	2	-	-	-	-	-	0	0		CVD
C2NC-120-100-350-01	12	9	35	11.6	107	1	12	2	-	-	-	-	-	0	0		CVD	

* further diameters on request

Cutting speed (V_c in m/min) | Feed per tooth (f_z) | d.o.c. (a_p) | w.o.c. (a_e)

Material	V _c (m/min)	a _p x d ₁ (mm)	a _e x d ₁ (mm)	Feed per tooth f _z (mm)							Cooling	Direction of feed
				Ø 2	Ø 3	Ø 4	Ø 6	Ø 8	Ø 10	Ø 12		
AlSi <12% Si	1800	0.6	0.3	0.01	0.02	0.02	0.04	0.06	0.08	0.1	Emulsion / MQL	climb milling
AlSi >12% Si	800	0.5	0.25	0.01	0.01	0.02	0.03	0.05	0.06	0.08		
Glass ceramic	250	0.2	0.3	0.025	0.035	-	-	-	-	-		
PMMA Acryl	1100	0.5	0.5	0.01	0.015	0.02	0.03	0.05	0.07	0.09	Emulsion recommended	climb milling
PF66 – GF30	700	0.5	0.3	0.008	0.01	0.015	0.025	0.04	0.06	0.08		
PEEK – GF30	700	0.5	0.25	0.007	0.008	0.01	0.02	0.03	0.05	0.07		
POM – GF30	800	0.5	0.5	0.008	0.01	0.015	0.025	0.04	0.06	0.08		
PTFE – GF30	700	0.5	0.3	0.01	0.015	0.02	0.03	0.05	0.07	0.09		
CFK	250	0.4	0.25	0.008	0.01	0.015	0.025	0.04	0.06	0.08	optionally air / MQL	climb milling / conventional milling
GFK	500	0.5	0.3	0.01	0.015	0.02	0.03	0.05	0.07	0.09		
AFK Aramid	300	0.45	0.3	0.01	0.015	0.02	0.03	0.05	0.07	0.09		
Zirkon	150	0.5	0.4	0.01	0.02	0.02	0.04	0.06	0.08	0.10		



**Pokolm
Frästechnik GmbH & Co. KG**

Adam-Opel-Straße 5
33428 Harsewinkel
Germany

fon: +49 5247 9361-0
fax: +49 5247 9361-99

info@pokolm.com
www.pokolm.com



www.pokolm.com